

10/611,693

1563/SYMBP155US

AMENDMENTS TO THE CLAIMS

This listing of Claims replaces all prior versions of claims in the application.

Listing of Claims:

1. (Currently amended) A portable data terminal comprising:
a bar code reader;
a flexible housing comprising a component rotatable about a junction of the housing and
~~having~~ an outer surface with energy absorbing material connected thereto for an initial
absorption of a physical shock energy exerted thereupon;
a stiff enclosure for at least partially encapsulating a circuit board; and
a resilient member interposed between the housing and the stiff enclosure, the resilient
frame and the stiff enclosure act together to further dampen the physical shock energy.
2. (Cancelled)
3. (Currently amended) The terminal of claim ~~[[2]]~~ 1, the flexible housing including a top
portion and a lower portion with the rotatable component as part of the top portion.
4. (Currently amended) The terminal of claim ~~[[2]]~~ 1, the junction being at a point of
connection between a handle of the data terminal and a base of the lower portion.
5. (Original) The terminal of claim 3, the handle comprising rubber insert molding.
6. (Original) The terminal of claim 3, the circuit board has a length shorter than a length of
the rotatable component.
7. (Original) The terminal of claim 1, the energy absorbing material comprising a raised
bumper assembly.

10/611,693

1563/SYMBP155US

8. (Currently amended) A method for mitigating physical shock energy exerted on a hand held terminal comprising:

rotating a portion of the hand held terminal housing about a junction of the housing, the junction being at a point of connection between a handle of the terminal and a base of a lower portion of the housing;

employing a bumper assembly placed on an outer surface of the hand held terminal housing to absorb an initial portion of the shock energy; and

employing an internal bumper system interposed between the housing and at least one circuit board within the housing, to further absorb the shock energy.

9. (Original) The method of claim 8 further comprising providing portions of the housing that are displaceable with respect to each other such that displacement of the portions further dampens the shock energy.

10. (Currently amended) A portable data terminal comprising:

a plurality of circuit boards mounted on a sub frame, being at least partially encased by a rigid body positioned within the terminal ~~housing~~ housing; and

a resilient member interposed between the rigid body and the housing, the resilient member and the rigid body for absorption of a physical shock energy exerted upon the terminal housing.

11. (Original) The portable data terminal of claim 10, the rigid body selected from the group consisting of metals and plastic.

12. (Original) The portable data terminal of claim 10, the resilient member forming an elastic frame around the rigid body.

13. (Original) The portable terminal according of claim 12, the rigid body shifts laterally within the resilient member, if the physical shock energy exceeds a predetermined level.

10/611,693

1563/SYMBP155US

14. (Original) The portable terminal of claim 10, the plurality of circuit boards including a unique circuit board being readily interchangeable at a manufacturing level as to enable a modular assembly of the portable terminal.
15. (Original) The portable terminal of claim 14, the rigid body comprising at least one rigid frame maintaining mounting points shared between the unique circuit board and other circuit boards.
16. (Original) The portable terminal of claim 14, the plurality of circuit boards being encased by the rigid frame as to maintain a substantially planar configuration when a physical shock is exerted on the portable terminal.
17. (Original) A portable data terminal comprising:
means for maintaining a planar configuration for a printed circuit board of the data terminal; and
means for absorbing a physical shock energy exerted on the data terminal.
18. (Original) A portable data terminal comprising:
a bar code reader,
a circuit board assembly enclosed within a flexible housing;
energy absorbing means attached to the flexible housing;
enveloping means for at least partially encasing the circuit board; and
resilient cushion means interposed between the housing and the enveloping means for reducing a shock energy level to a level acceptable by the circuit board assembly.

10/611,693

1563/SYMBP155US

19. (Currently amended) A method for manufacturing a plurality of bar code reading mobile terminal types, comprising:

providing common components for the mobile terminal types that are respectively generic to the types; [[and]]

assembling a particular mobile terminal type by at least a subset of the respective common components;

receiving a customer order for a specific mobile terminal type, and fabricating the specific type via employment of the common and unique components; and

providing a rigid frame having mounting parts shared between circuit boards of the common and unique components, the rigid frame for maintaining a planar configuration of the circuit boards.

20. (Original) The method of claim 19, further comprising assembling the particular mobile terminal type by components that are unique for the particular mobile terminal.

21. (Cancelled)

22. (Currently amended) The method of claim [[21]] 19, further comprising providing a generic shock assembly connected to an outer surface of the housing.

23. (Cancelled)

24. (Currently amended) The method of claim [[23]] 19, further comprising:
providing a resilient member interposed between the housing and the rigid frame for reducing a shock energy level to a level acceptable by the circuit boards.